



## NEW GOZZO 45 MAIN FEATURES

- Head-turning design with strong personality
- Genuine walk-around: no steps, large side-walks, high bulwarks
- Best in class liveability inside/outside with wider beam and 24mq cockpit
- Driving seats x 4 with integrated wet-bar, table for 8/10 guests
- 2 x generous sun-pads plus bow lounge
- Vast beach-area with hi/low platform
- 2 or 3 cabins, 2 heads + dinette with L-shape sofa
- Great marine attitude: seakeeping, stability and comfort
- Highest level of customization on the market

















































## apreamare Gozzo®






Standard layout



Optional layout



## PRELIMINARY TECHNICAL DATA

## 1 ENGINES

| 2* CUMMINS QSC8,3 600 mhp/441kW at 3000 rpm               | STD        |              |              |
|---|------------|--------------|--------------|
| 2 * VOLVOPENTA IPS 1 - 650 435 mhp / 320 kw at 3700 g/min | OPT        |              |              |
|   |            |              |              |
| 2 SPEED (knots)   | QSC8.3 600 |              | VP IPS 650   |
| Maximum speed at medium load displacement                 | 30         | knots        | 33           |
| Cruising speed at medium load displacement                | 25         | knots        | 27           |
|   |            |              |              |
| 3 RANGE (nautical miles)                                  | QSC8.3 600 |              | VP IPS 650   |
| Maximum speed   | 192        | n.m.         | 278          |
| Cruising speed  | 241        | n.m.         | 350          |
|   |            |              |              |
| 4 MAIN SIZES  |            |              |              |
| Loa = overall length (standard ISO 8666)                  | 14,70      | m.           | 48 ft. 3 in. |
| Lh = Hull length (standard ISO 8666)                      | 13,00      | m.           | 42 ft. 8 in. |
| Lg = waterline length (boat fully laden)                  | 12,55      | m.           | 41 ft. 2 in. |
| Max. beam   | 4,70       | m.           | 15 ft. 5 in. |
| Depth under propellers (boat fully laden)                 | 1,20       | m.           | 3 ft. 11 in. |
| Displacement unladen                                      | 15,9       | ton./lb.     | 35053        |
| Displacement laden  | 19,0       | ton./lb.     | 41888        |
| Max.number of persons on board                            | 16         |              |              |
| Navigation category CE 2003/44                            | В          |              |              |
| Certification modules                                     | В          |              |              |
|   |            |              |              |
| 5 TECHNICAL DATA  |            |              |              |
| Hull type: deadrise. Warped hull with spray rails         |            |              |              |
| H t = Minimum transport height under propellers           | 4,75       | m.           | 15 ft. 7 in. |
| Fuel tank capacity  | 1600       | lt./US gals. | 423          |
| Fresh water tank capacity                                 | 350        | lt./US gals. | 92           |
| Black water tank capacity                                 | 77         | lt./US gals. | 20           |
|   |            |              |              |

Technical data, performance and range figures, designs and graphic reproductions contained herein have no certification value. They are purely descriptive and refer to standard models. Actual technical or descriptive specifications must be provided solely with regards to the craft being purchased. Therefore, any indications will be binding for the seller only if contained in the sales contract and in the relevant manual







Via Terragneta, 72 80058 Torre Annunziata (NA) Tel: +39 081 537 8411 info.apreamare@apreamare-yacht.com

www.apreamare.it